



# PRESS EQUIPMENT

**Patent number:** JP2002144098  
**Publication date:** 2002-05-21  
**Inventor:** FUTAMURA SHOJI; KANEKO HIROMITSU  
**Applicant:** INST TECH PRECISION ELECT  
**Classification:**  
**- international:** *B30B1/18; B30B1/40; B30B15/00; B30B1/00; B30B15/00;* (IPC1-7): B30B15/14; B30B1/18; B30B15/06  
**- european:** B30B1/18; B30B1/40; B30B15/00D2  
**Application number:** JP20000339304 20001107  
**Priority number(s):** JP20000339304 20001107

Also published as:

 EP1332866 (A1)  
 WO0238366 (A1)  
 US6679164 (B2)  
 US2002178938 (A1)  
 CA2396092 (A1)

Report a data error here

## Abstract of JP2002144098

**PROBLEM TO BE SOLVED:** To provide press equipment for fixed point working which is simple in structure and is easy to manufacture.

**SOLUTION:** The press equipment comprises a flat planar substrate 1, a guide body 2 of which the one-side end intersects orthogonally with this substrate, a supporting plate 3 which intersects orthogonally with the other end of the guide body, a screw shaft 5 which is supported at this supporting plate in parallel with the guide body a nut member 8 screwed with the screw shaft 5 and movable bodies 7. The movable bodies are formed of first and second movable bodies 71 and 72 which are arranged to face each other. These first and second movable bodies are connected by a differential member 27 and the first and second movable bodies are relatively moved by the movement of this differential member in the orthogonal direction to the moving direction of the movable bodies.

